



BALAD

3602 - SET OF 3 LAMPS H.12 CM
 DESIGN BY TRISTAN LOHNER

DOMESTIC | PROFESSIONAL | INTENSIVE



Polyethylene diffuser
 Aluminium frame
 ABS base
Technology: integrated LED - Luminous flux: 20 lm
Switch type: push button
Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)
Lighting mood:
 Position 1 cool white (6000°K) 100% brightness
 Position 2 neutral white (4000°K) 100% brightness
 Position 3 candle-style warm white (2300°K) flickering
Type of power supply: battery - Min. Battery life (100%): 10 h
Battery use cycle: 500 cycles
Recharge time: 4h - Type of recharge: USB, cable (supplied) 1,5m
 Bypass to prevent battery damage during wired use
 0.25 A - 5 V - 0.3 W | IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA
 Powered by Smart & Green



0.15 kg


- | | |
|---------------------|------------------------|
| 360282 ● Cactus | 360221 ● Acapulco Blue |
| 360214 ● Nutmeg | 360220 ● Red Ochre |
| 360273 ● Honey | 3602B9 ● Black Cherry |
| 360247 ● Anthracite | 3602A5 ● Clay Grey |

3612 - LAMP H.25 CM
 DESIGN BY TRISTAN LOHNER

DOMESTIC | PROFESSIONAL | INTENSIVE



Polyethylene diffuser
 Aluminium frame
 ABS base
Technology: integrated LED - Luminous flux: 40 lm
Switch type: push button
Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)
Lighting mood:
 Position 1 cool white (6000°K) 100% brightness
 Position 2 neutral white (4000°K) 100% brightness
 Position 3 neutral white (4000°K) 50% brightness
 Position 4 candle-style warm white (2300°K) flickering
Type of power supply: battery - Min. Battery life (100%): 7 h
Battery use cycle: 300 cycles
Recharge time: 5h - Type of recharge: USB, cable (supplied) 2m
 Bypass to prevent battery damage during wired use
 0.5 A - 5 V - 0.5 W | IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA
 Powered by Smart & Green




0.53 kg

- | | |
|------------------------|-----------------------|
| 361282 ● Cactus | 361220 ● Red Ochre |
| 361273 ● Honey | 3612B9 ● Black Cherry |
| 361247 ● Anthracite | 3612A5 ● Clay Grey |
| 361221 ● Acapulco Blue | |

BALAD

3622 - LAMP H.38 CM
 DESIGN BY TRISTAN LOHNER

DOMESTIC | PROFESSIONAL | INTENSIVE



Polyethylene diffuser
 Aluminium frame
 ABS base

Technology: integrated LED - Luminous flux: 150 lm

Switch type: push button

Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)

Lighting mood:

Position 1 cool white (6000°K) 100% brightness

Position 2 cool white (6000°K) 50% brightness

Position 3 neutral white (4000°K) 100% brightness

Position 4 neutral white (4000°K) 50% brightness

Position 5 candle-style warm white (2300°K) flickering

Type of power supply: battery - Min. Battery life (100%) 9 h

Battery use cycle: 300 cycles


Recharge time: 7h - Type of recharge: USB, cable (supplied) 2m

Bypass to prevent battery damage during wired use

2 A - 5 V - 2.5 W | IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA

Energy rating: E

Powered by Smart & Green



1.21 kg

- 362282 ● Cactus
- 362273 ● Honey
- 362247 ● Anthracite
- 362221 ● Acapulco Blue

- 362220 ● Red Ochre
- 3622B9 ● Black Cherry
- 3622A5 ● Clay Grey



BALAD

BALAD

3632 - SPIKE STAND
DESIGN BY TRISTAN LOHNER

DOMESTIC PROFESSIONAL INTENSIVE 6⁷ IPAC



Steel wire frame
Steel clip on the ball joint system, with protective rubber pads
Compatible with:
LAMP H.25 CM - BALAD
LAMP H.38 CM - BALAD

- | | |
|------------------------|-----------------------|
| 363282 ● Cactus | 3632B9 ● Black Cherry |
| 363247 ● Anthracite | 3632A5 ● Clay Grey |
| 363221 ● Acapulco Blue | 3632C6 ● Honey |
| 363220 ● Red Ochre | |



3631 - UPRIGHT STAND
DESIGN BY TRISTAN LOHNER

DOMESTIC PROFESSIONAL INTENSIVE 7 IPAC




Steel wire frame
Steel ballast
Steel clip with protective rubber pads
Compatible with:
LAMP H.25 CM - BALAD
LAMP H.38 CM - BALAD

- | | |
|------------------------|-----------------------|
| 363182 ● Cactus | 3631B9 ● Black Cherry |
| 363147 ● Anthracite | 3631A5 ● Clay Grey |
| 363121 ● Acapulco Blue | 3631C6 ● Honey |
| 363120 ● Red Ochre | |




3630 - OFFSET STAND
DESIGN BY TRISTAN LOHNER

DOMESTIC PROFESSIONAL INTENSIVE 7 IPAC



Steel wire frame
Steel ballast
Steel clip, with protective rubber pads
Compatible with:
LAMP H.38 CM - BALAD
LAMP H.25 CM - BALAD

- | | |
|------------------------|-----------------------|
| 363082 ● Cactus | 3630B9 ● Black Cherry |
| 363047 ● Anthracite | 3630A5 ● Clay Grey |
| 363021 ● Acapulco Blue | 3630C6 ● Honey |
| 363020 ● Red Ochre | |




Recommendations for appropriate installations:

Choose Balad H.25 cm with:



Choose Balad H.38 cm with:






BALAD

LIGHTING

BALAD

365100 - SET OF 3 LAMPS BAMBOO H.12 CM

DESIGN BY TRISTAN LOHNER



Polyethylene diffuser
Bamboo frame
ABS base

Technology: integrated LED - Luminous flux: 20 lm

Switch type: push button

Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)

Lighting mood:

Position 1 cool white (6000°K) 100% brightness

Position 2 neutral white (4000°K) 100% brightness

Position 3 candle-style warm white (2300°K) flickering

Type of power supply: battery - Min. Battery life (100%): 10 h


Battery use cycle: 500 cycles

Recharge time: 4h - Type of recharge: USB, cable (supplied) 1,5m

Bypass to prevent battery damage during wired use

0.25 A - 5 V - 0.3 W - IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA

Powered by Smart & Green



0.13 kg

365200 - LAMP BAMBOO H.25 CM

DESIGN BY TRISTAN LOHNER



Polyethylene diffuser
Bamboo frame
ABS base

Technology: integrated LED - Luminous flux: 40 lm

Switch type: push button

Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)

Lighting mood:

Position 1 cool white (6000°K) 100% brightness

Position 2 neutral white (4000°K) 100% brightness

Position 3 neutral white (4000°K) 50% brightness

Position 4 candle-style warm white (2300°K) flickering

Type of power supply: battery - Min. Battery life (100%): 7 h


Battery use cycle: 300 cycles

Recharge time: 5h - Type of recharge: USB, cable (supplied) 2m

Bypass to prevent battery damage during wired use

0.5 A - 5 V - 0.5 W - IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA

Powered by Smart & Green



0.47 kg

BALAD

365300 - LAMP BAMBOO H.38 CM
DESIGN BY TRISTAN LOHNER



Polyethylene diffuser
Bamboo frame
ABS base

Technology: integrated LED - Luminous flux: 150 lm

Switch type: push button

Function of the switch: change the light temperature & brightness (short click, 1 s), OFF (long click, 3 s)

Lighting mood:

Position 1 cool white (6000°K) 100% brightness

Position 2 cool white (6000°K) 50% brightness

Position 3 neutral white (4000°K) 100% brightness

Position 4 neutral white (4000°K) 50% brightness

Position 5 candle-style warm white (2300°K) flickering

Type of power supply: battery - Min. Battery life (100%): 9 h

Battery use cycle: 300 cycles


Recharge time: 7h - Type of recharge: USB, cable (supplied) 2m

Bypass to prevent battery damage during wired use

2 A - 5 V - 2.5 W - IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA

Energy rating: E

Powered by Smart & Green



1.08 kg

