


MOON!

5303 - LAMP H.41 CM
DESIGN BY TRISTAN LOHNER



Polyethylene diffuser
Aluminium frame
ABS base

Technology: integrated LED - **Luminous flux:** 150 lm

Switch type: dimmer

Function of the switch: change the brightness (10 to 100%, click 4 s), change the light temperature (double short click), ON/OFF (short click, 1s)

Lighting mood:

Position 1 cool white (6000°K) dimmer switch (10 to 100%)

Position 2 warm white (3000°K) dimmer switch (10 to 100%)

Type of power supply: battery - **Min. Battery life (100%):** 8 h

Battery use cycle: 300 cycles

Recharge time: 7h - **Type of recharge:** USB, cable (supplied) 2m

Bypass to prevent battery damage during wired use

2 A - 5 V - 2.5 W - IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA

Energy rating: F

Powered by Smart & Green




0.7 kg

- 530382 ● Cactus
- 530373 ● Honey
- 530314 ● Nutmeg
- 530347 ● Anthracite

- 530321 ● Acapulco Blue
- 530320 ● Red Ochre
- 5303A5 ● Clay Grey
- 5303B9 ● Black Cherry

5304 - LAMP H.41 MAX
DESIGN BY TRISTAN LOHNER



Glass diffuser
Aluminium frame
ABS base

Technology: integrated LED

Luminous flux on battery: 200 lm - **Luminous flux on mains:** 300 lm

Switch type: touch-activated dimmer

Function of the switch: change the brightness (10 to 100%, click 4 s), change the light temperature (double short click), ON/OFF (short click, 1s)

Lighting mood:

Position 1 warm white (2700°K) dimmer switch (10 to 100%)

Position 2 neutral white (4000°K) dimmer switch (10 to 100%)

Min. Battery life (100%): 7 h - **Battery use cycle:** 300 cycles


Recharge time: 7h - **Type of recharge:** USB Fermob magnet – 1.5 m cable (provided)

Bypass to prevent battery damage during wired use

2 A - 5 V - 3 W - IP44 (ingress protection) | IK 0 (impact resistance) | CE | FCC

Energy rating: F

Powered by Smart & Green



1 kg

- 5304B9 ● Black Cherry
- 530482 ● Cactus

- 530421 ● Acapulco Blue
- 530447 ● Anthracite

Watch our video



Fermob
magnet



- Charging system
- Practical & easy to use
- Identifiable (due to samara)




	LAMP H.41 MAX	LAMP H.41
Diffuser	Glass	Polyethylene
Lighting power	200 to 300 lm	150 lm
Colour temperatures	2700°K + 4000°K	3000°K + 6000°K
Switch	Touch - activated dimmer	Dimmer
Recharge	USB induction with its Fermob magnet	USB
Battery life	7h	8h



MOON!

5320 - LAMP H.63 CM
DESIGN BY TRISTAN LOHNER

DOMESTIC | PROFESSIONAL | INTENSIVE



Polyethylene diffuser
Aluminium frame
ABS base

Technology: integrated LED - Luminous flux: 500 lm

Switch type: touch-activated

Function of the switch: change the light temperature (long click, 3 s), change the brightness (short click, 1 s), Reset Bluetooth pairing (click and hold for 10 s)

Lighting mood:

Position 1 cool white (6000°K) 50% brightness
Position 2 cool white (6000°K) 100% brightness
Position 3 warm white (3000°K) 50% brightness
Position 4 warm white (3000°K) 100% brightness

Lighting mood via Bluetooth:

White light variable from 6000°K to 3000°K & dimmer switch (10% to 100%)

Type of power supply: battery - Min. Battery life (100%) 7 h

Battery use cycle: 300 cycles

Recharge time: 4h - Type of recharge: ABS plastic charging base & transformer

I 10-230 Apv*-24 Dpv** IPX0, powered by mains electricity

Plug type : 4 plugs multi-type (J, K, G, F, L, E, B, I)

Bypass to prevent battery damage during wired use

1.5 A - 24 V - 7 W - IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC


Energy rating: F

Powered by Smart & Green

Compatible with:

FERMOB LIGHTING APPLICATION - FERMOB LIGHTING

SMART SWITCH - LUDO



2.65 kg

- 532082 ● Cactus
- 5320B9 ● Black Cherry
- 532047 ● Anthracite

- 532021 ● Acapulco Blue
- 532020 ● Red Ochre




* Alternating power volt / **Direct power volt

MOON!

5310 - LAMP H.134 CM
DESIGN BY TRISTAN LOHNER

DOMESTIC | PROFESSIONAL | INTENSIVE



Polyethylene diffuser
Aluminium frame
ABS base

Technology: integrated LED - Luminous flux: 500 lm

Switch type: touch-activated

Function of the switch: change the light temperature (long click, 3 s),
change the brightness (short click, 1 s), Reset Bluetooth pairing
(click and hold for 10 s)

Lighting mood:

Position 1 cool white (6000°K) 50% brightness
Position 2 cool white (6000°K) 100% brightness
Position 3 warm white (3000°K) 50% brightness
Position 4 warm white (3000°K) 100% brightness

Lighting mood via Bluetooth:

White light variable from 6000°K to 3000°K & dimmer switch (10% to 100%)

Type of power supply: battery - Min. Battery life (100%) 7 h

Battery use cycle: 300 cycles

Recharge time: 4h - Type of recharge: ABS plastic charging base & transformer

I 10-230 Apv*-24 Dpv** IPX0, powered by mains electricity

Plug type: 4 plugs multi-type (J, K, G, F, L, E, B, I)

Bypass to prevent battery damage during wired use

1.5 A - 24 V - 7 W - IP44 (ingress protection) | IK 10 (impact resistance) | CE | FCC | UKCA


Energy rating: F

Powered by Smart & Green

Compatible with:

FERMOB LIGHTING APPLICATION - FERMOB LIGHTING

SMART SWITCH - LUDO



5.4 kg

- 531082 ● Cactus
- 531089 ● Black Cherry
- 531047 ● Anthracite

- 531021 ● Acapulco Blue
- 531020 ● Red Ochre




* Alternating power volt / **Direct power volt

MOON!

5330 - WALL LIGHT Ø15 CM

DESIGN BY TRISTAN LOHNER

DOMESTIC | PROFESSIONAL | INTENSIVE



Glass diffuser
Aluminium frame
Recycled ABS base
Technology: integrated LED - Luminous flux: 400 lm

Lighting mood:

Position I warm white (3000°K) 100% brightness

Lighting scenario via Bluetooth:

White light variable from 6000°K to 3000°K & dimmer switch (10% to 100%)

Type of fastening: Quick'n'click for fast installation with a single quarter turn (integrated spirit level and detachable base)

Type of power supply: wall mount | 0.24 A - 230 V - 8 W

IP54 (ingress protection) | IK 0 (impact resistance) | CE | UKCA


Energy rating: F

Powered by Smart & Green

Compatible with:

FERMOB LIGHTING APPLICATION - FERMOB LIGHTING

SMART SWITCH - LUDO



0.9 kg

- 533082 ● Cactus
- 533047 ● Anthracite
- 533021 ● Acapulco Blue

- 533020 ● Red Ochre
- 5330B9 ● Black Cherry

Watch our video



MOON!



quick'n clic

Easy installation



Watch our video



MOON!



LIGHTING

MOON!

5340 - TRIPLE PENDANT LIGHTS Ø15 CM

DESIGN BY TRISTAN LOHNER



Glass diffuser
Aluminium frame
Recycled ABS base

Technology: integrated LED - Luminous flux: 1050 lm

Function of the switch: change the light temperature (click 1 s),
change the brightness (10 to 100%, click 4 s), ON/OFF (short click, 1 s)

Lighting mood:

Position 1 cool white (6000°K) dimmer switch (10 to 100%)

Position 2 warm white (3000°K) dimmer switch (10 to 100%)

Lighting scenario via Bluetooth:

White light variable from 6000°K to 3000°K & dimmer switch (10% to 100%)

Type of fastening: Quick'n'click for fast installation with a single quarter turn (detachable base)

Type of power supply: wired

Adjustable cable

0.19 A - 230 V - 17 W - IP42 (ingress protection) | IK 0 (impact resistance) | UKCA

Energy rating: E

Powered by Smart & Green

Compatible with:

FERMOB LIGHTING APPLICATION - FERMOB LIGHTING


SMART SWITCH - LUDO

5340B9 ● Black Cherry

534021 ● Acapulco Blue

534082 ● Cactus

534047 ● Anthracite



2.5 kg

Watch our video



5350 - PENDANT LIGHTS Ø25 CM

DESIGN BY TRISTAN LOHNER



Glass diffuser
Aluminium frame
Recycled ABS base

Technology: integrated LED - Luminous flux: 1000 lm

Function of the switch: change the light temperature (click 1 s),
change the brightness (10 to 100%, click 4 s), ON/OFF (short click, 1 s)

Lighting mood:

Position 1 cool white (6000°K) dimmer switch (10 to 100%)

Position 2 warm white (3000°K) dimmer switch (10 to 100%)

Lighting scenario via Bluetooth:

White light variable from 6000°K to 3000°K & dimmer switch (10% to 100%)

Type of fastening: Quick'n'click for fast installation with a single quarter turn (detachable base)

Type of power supply: wired

Adjustable cable

0.19 A - 230 V - 15 W - IP42 (ingress protection) | IK 0 (impact resistance) | UKCA

Energy rating: E

Powered by Smart & Green

Compatible with:

FERMOB LIGHTING APPLICATION - FERMOB LIGHTING


SMART SWITCH - LUDO

5350B9 ● Black Cherry

535021 ● Acapulco Blue

535082 ● Cactus

535047 ● Anthracite



2 kg

Watch our video

